




PARKING LOT CONTROLLER WITH ENERSAVE LOGIC & MAIN CONTACTOR

VPC-DA

The VPC-DA Parking Lot Controller uses the Enersave logic to control multiple set points for parking lot applications. The weather proof design is ideal for outdoor use. Standard PC101 grey powder coat paint provides a durable finish. This line of Parking Lot Controller is designed for applications where distribution is in a separate location.



Features/Specifications

- Steel construction
- CSA Type 3R rated
- Pad lockable draw latch(es)
- Enersave Temperature Controller with:
 - Up to (4) set points customer programmable temperature set points (recommended -5°C, -10°C, -15°C, -20°C)
 - Programmable number of set points
 - Duration of cycle
 - Supervisory Enable Signal
- Easy field configuration via jumper settings
- Standard 120/208V 3 Phase
- HOA switch to bypass logic
- Temperature sensing cable with weather proof cover
- 3 pole main contactor
- Wall mounted enclosure
- PC101 Grey powder coat finish

Optional Items

- Pad mount design
- Higher amperage ratings
- Single phase (120/240V)
- Time of day clock
- Aluminum or stainless steel construction
- CSA type 1, 4 or 4X rated
- Remote sensing thermostat
- Custom powder coat colours

PART NUMBER	MAIN CONTACTOR AMPS
VPC-DA-60	60
VPC-DA-75	75
VPC-DA-90	90
VPC-DA-115	115
VPC-DA-150	150
VPC-DA-185	185
VPC-DA-225	225
VPC-DA-265	265