




**PARKING LOT CONTROLLER WITH ENERSAVE LOGIC,
DISTRIBUTION PANEL & SECONDARY 3POLE CONTACTORS**

VPC-DE

The VPC-DE Parking Lot Controller uses the Enersave logic to control multiple set points for parking lot applications. The weather proof design is ideal for outdoor use. Standard PC101 grey powder coat paint provides a durable finish. This line of Parking Lot Controller is all encompassing with the breaker panel and secondary contactors located in a single pad mount enclosure.



Features/Specifications

- Steel construction
- CSA Type 3R rated
- Pad lockable handle
- Enersave Temperature Controller with:
 - Up to (4) set points customer programmable temperature set points (recommended -5°C, -10°C, -15°C, -20°C)
 - Programmable number of set points
 - Duration of cycle
 - Supervisory Enable Signal
- Easy field configuration via jumper settings
- 50/50 load share
- Standard 120/208V 3 Phase
- HOA switch to bypass logic
- Temperature sensing cable with weather proof cover
- Circuit breaker panel
- 35A resistive 3Pole contactors
- Pad mount design
- PC101 Grey powder coat finish

PART NUMBER	BREAKER PANEL AMPS	BREAKER PANEL CIRCUITS
VPC-DE-100-12-xx	100	12
VPC-DE-100-18-xx	100	18
VPC-DE-100-30-xx	100	30
VPC-DE-225-30-xx	225	30
VPC-DE-225-42-xx	225	42
VPC-DE-225-72-xx	225	72
VPC-DE-225-84-xx	225	84
VPC-DE-400-30-xx	400	30
VPC-DE-400-42-xx	400	42
VPC-DE-400-72-xx	400	72
VPC-DE-400-84-xx	400	84
VPC-DE-600-30-xx	600	30
VPC-DE-600-42-xx	600	42
VPC-DE-600-84-xx	600	84

Optional Items

- Wall mount enclosure
- Higher amperage ratings
- Single phase (120/240V)
- Time of day clock
- Aluminum or stainless steel construction
- CSA type 1, 4 or 4X rated
- Remote sensing thermostat
- Custom powder coat colours

xx = Number of secondary contactor poles. (e.g. VPC-DE-400-30-**36**)