



## BC HYDRO METERING KIOSK

### BCH

Metering kiosk built to BC Hydro distribution standards. Used for applications where secondary services are installed in weatherproof kiosks outside of a main facility.



Features/Specification:

- Marine grade aluminum construction
- CSA Type 3R rated
- Padmount design
- Double roof design for solar shielding
- Padlockable stainless steel 3-point handle
- Hinged doors with pour in place gasket
- Hidden hinges for additional security
- Gas shock door stays
- Removable lifting ears
- Viewing window on door (Models up to 800A)
- PC101 (ANSI 61) Grey powder coat finish
- Service entrance rated main breaker
- Utility approved CT enclosure
- Compliant with BCH metering standards
- Complete factory wiring for line & load lugs
- \*Models above 800A have external meter bases and bussed CT section

Options:

- Custom powder coat colours
- Stainless steel construction
- Door switch, light, thermostat, heater, fan
- Insulation
- Convenience receptacle
- Additional sizes and configurations

PART NUMBER	MAIN BREAKER	PHASE	VOLTAGE
BCH-400-1-240	400A	1	120/240V
BCH-600-1-240	600A	1	120/240V
BCH-800-1-240	800A	1	120/240V
BCH-400-3-208	400A	3	120/208V
BCH-600-3-208	600A	3	120/208V
BCH-800-3-208	800A	3	120/208V
BCH-400-3-600	400A	3	347/600V
BCH-600-3-600	600A	3	347/600V
BCH-800-3-600	800A	3	347/600V
BCH-1000-3-600*	1000A	3	347/600V
BCH-1200-3-600*	1200A	3	347/600V
BCH-1600-3-600*	1600A	3	347/600V